## Hammer Mounted Auto Lube

Model G015 compatible with PH-3, PH-4 & GH-6 Hammers Model G025 compatible with GH-7, GH-9, GH-10, GH-12, GH-15, GH-18, GH-23, GH-30 & GH-40 Hammers



Output from 0.8 to 1.44 lb/hr

- Increase Hammer Versatility
- Reduce Maintenance Cost
- Greater Productivity
- Hydraulically Driven, Automatically Providing a <u>Continuous</u> Supply of Grease while Hammer is Running
  Reliable Even in Low Temperatures
  Suitable for Special Lubricants Including Copper Based Pastes
  All NPK Auto Lube Systems Include Mounting Hardware and Adapter Fittings
- Various Cartridge Adapters Available for Conforming to Different Size Grease Tubes
  Cartridge Refill Adapter
  - Provided with Pump for Refilling Grease Tubes

NPK ATTACHMENTS...designed, built and backed by NPK.

## CARRIER MOUNTED AUTO LUBES

| NPK Hammer/Auto Lube Compatibility |          |      |   |       |          |       |          |   |                |              |       |          |                     |  |
|------------------------------------|----------|------|---|-------|----------|-------|----------|---|----------------|--------------|-------|----------|---------------------|--|
|                                    | PH-3     | PH-4 |   | GH-7  |          | GH-10 |          | - |                | GH-23        | GH-30 | GH-40    | GH-50               |  |
| G-075                              |          |      |   |       |          |       |          |   |                |              |       |          |                     |  |
| G-075L                             | <b>E</b> |      |   |       |          |       |          |   |                |              |       |          |                     |  |
| G-100                              |          |      |   |       |          |       |          |   |                |              |       |          |                     |  |
| G-100L                             |          |      | 1 |       | <b>N</b> |       |          |   |                |              |       |          |                     |  |
| G-150                              |          |      |   |       |          |       | <b>N</b> |   |                |              |       |          |                     |  |
| G-150L                             |          |      |   |       |          |       |          |   | Shared a state |              |       |          |                     |  |
| <b>G-15</b> 3                      |          |      |   |       |          |       |          |   |                |              |       |          |                     |  |
| G-153L                             |          |      |   |       |          |       |          |   |                |              |       |          |                     |  |
| G-175                              |          |      |   |       |          |       |          |   |                |              |       |          |                     |  |
| G-175L                             |          |      |   |       |          |       |          |   |                |              |       | 1        |                     |  |
| G-186                              |          |      |   |       |          |       |          |   |                |              |       | 1        | Will Will Will Will |  |
| G-186L                             |          |      |   |       |          |       |          |   |                |              |       | <b>N</b> |                     |  |
|                                    | G-075    |      |   | G-100 |          |       | G-150    |   |                | <b>G-153</b> |       |          |                     |  |

## Auto Lube Features

- All NPK Auto Lube Systems include mounting hardware and adapter fittings for hammer.
- Automatically provides a continuous supply of grease while hammer is running.
- L Models come with a low level switch that activates a warning light and buzzer in the cab, and can be wired (on solenoid energized circuits) to shut off hammer when insufficient grease levels are detected.
- High pressure pump capable of pumping EP2 grease in cold weather.
- Six (6) month Base Warranty, twelve (12) month Extended Warranty.

|                      | <b>G-075</b> | G-100    | G-150    | G-153      | G-175      | G-186      |
|----------------------|--------------|----------|----------|------------|------------|------------|
| Reservoir            |              |          |          |            |            |            |
| Capacity             | 4.4 lbs.     | 8.8 lbs. | 8.8 lbs. | 17.6 lbs.  | 8.8 lbs.   | 17.6 lbs.  |
| Maximum<br>Output/Hr | 1/2 lb.      | 1/2 lb.  | 1 lb.    | 1 1/2 lbs. | 1 1/2 lbs. | 1 1/2 lbs. |

It is imperative that special lubricants be used in your NPK hammer to protect the main components. NPK grease products contain additives that resist extreme pressures and heat. Our specially formulated moly based grease and chisel paste are available through your local NPK dealer. NPK lubricants are offered in 14oz. cartridges, 35lb. pails, 120lb. kegs, 400lb. drums, or refillable cartridges for hammer mounted auto lube systems.



NPK Construction Equipment, Inc. 7550 Independence Drive Walton Hills, OH 44146-5541 Phone (440) 232-7900 Toll-free (800) 225-4379 Fax (440) 232-4382 Internet: www.npkce.com

Each product sold by NPK is subject to an express written warranty. NPK makes no other warranty, express or implied, including any warranty of merchantability of fitness for any particular purpose. NPK is not liable for any incidental or consequential damages.