Three models to choose from C-6CSD, C-8CSD, and C-10CSD

Sheet Pile Driver



Simple operation means that any excavator operator can easily drive and extract piles

180° free rotation allows precise alignment and positioning of sheet pile without having to reposition the machine

Fitted with a hydraulic cylinder lock for positive sheeting and pile clamping to prevent slippage

Rubber shock mounts to isolate vibration and reduce noise

NPK ATTACHMENTS...designed, built and backed by NPK.

SHEET PILE DRIVER Powerful downward vibration forces

for more precision and productivity

Superior Productivity

The NPK sheet piler uses the industry's leading compactors to develop powerful vibration forces for driving sheeting. The design of the sheet piler directs impulse forces downwards providing optimal driving of the pile. Durable rubber shock mounts protect the excavator boom and stick from vibration and shock loading.

Features

- 180° free rotation allows precise alignment and positioning of the sheet pile without having to reposition the machine. When not needed, the swivel can be locked in place; either parallel or perpendicular to the boom.
- Dedicated top mounting brackets designed to OEM bucket specifications provide a full range of motion for positioning to pick up/remove the sheet from the ground.
- Simple operation means that any excavator operator can easily drive and extract piles.
- Fitted with a hydraulic cylinder lock for positive sheeting and pile clamping to prevent slippage.
- Rubber shock mounts to isolate vibration and reduce noise.
- Heavy duty, high efficiency gear motor.
- Integrated flow control and pressure relieving valves protect the compactor motor from excessive flow and pressure.
- Oil splash lubrication eliminates routine greasing of the compactor bearing.

Excellent Versatility

The mobility and maneuverability of the excavator mounted NPK sheet piler permits operation in many previously confined or inaccessible areas: under low clearance obstructions (bridges, etc.), around bridge piers, and next to walls. All models have 180° degrees of free rotation and are equipped with dedicated top mounting brackets that provide a full working range. This makes it easy to pick up/remove and align the sheet in the correct position before driving/extracting.

Specifications			
NPK Model	C-6CSD	C-8CSD	C-10CSD
Impulse Force	16,000 lbf	24,000 lbf	34,000 lbf
Chuck Opening	1.5 in	1.5 in	1.5 in
Chuck Oil Flow	3-5 gpm	3-5 gpm	3-5 gpm
Chuck Pressure	3045 psi	3045 psi	3045 psi
Cycles per Minute	2200	2200	2200
Oil Flow	33 gpm	43 gpm	51 gpm
Operating Pressure	1800-2300 psi	2000-2500 psi	2000-2500 psi
Weight	2150 lb	2750 lb	4130 lb
Height	64 in	67 in	81 in
Width	23 in	25 in	33 in
Recommended Carrier Weight	16,000-42,000 lb	30,000-65,000 lb	60,000-100,000 lb

Weight does not include mounting bracket. Specifications subject to change without notice.







NPK Construction Equipment, Inc. 7550 Independence Drive Walton Hills, OH 44146-5541 Phone (440) 232-7900 Toll-free (800) 225-4379 Fax (440) 232-4382 Internet: www.npkce.com

Each product sold by NPK is subject to an express written warranty. NPK makes no other warranty, express or implied, including any warranty of merchantability of fitness for any particular purpose. NPK is not liable for any incidental or consequential damages.